

Table of Contents

Preface	11
Introduction	13
1 Scope.....	14
2 Normative References.....	14
2.1 Related HART Documents	14
2.2 Related Communication Documents	14
2.3 Other Related Documents	14
3 Definitions	15
4 Symbols and Abbreviations	20
5 Physical Device Types.....	21
5.1 Low Impedance Devices	21
5.2 High Impedance Devices	21
5.3 Device Connection Types	22
5.3.1 Current Input (Formerly Primary Master)	23
5.3.2 Current Output (Formerly Type C Field Device)	24
5.3.3 Voltage Input (New)	24
5.3.4 Voltage Output (Formerly Voltage Mode Slave Device)	24
5.3.5 Secondary (Formerly Secondary Master ¹)	24
5.3.6 Transmitter (Formerly Type A or B slave device)	25
5.3.7 Actuator (New)	25
5.3.8 Non -DC Isolated Bus (Formerly Type A slave in multi-drop mode ¹)	25
5.3.9 DC Isolated Bus Device (Formerly Type D Field Device ¹)	25
6 Network Configuration Rules.....	26
6.1 Definitions of Elements	26
6.2 Combination of Elements	26
6.2.1 Rule Number 1	26
6.2.2 Rule Number 2	26
6.2.3 Rule Number 3	26
6.2.4 Rule Number 4	26
6.2.5 Rule Number 5	26
6.3 Example Topologies	27
6.3.1 Point to Point Current Input	27
6.3.2 Point to Point Current Output	28
6.3.3 Multi-drop	29

6.3.4	Multi-drop with Analog Signaling	30
6.3.5	Series Connection	31
7	Common Characteristics of All Device Types	33
7.1	Digital Signaling Requirements	33
7.1.1	Digital Signaling Spectrum	33
7.1.2	Digital Signaling Characteristics	33
7.1.3	Transmitted Waveform	35
7.1.4	Receiver Characteristics	36
7.2	Analog Signaling Requirements	37
7.2.1	Analog Signaling Spectrum	37
7.2.2	Analog Signaling Interference on Digital Signaling	38
7.2.3	Analog Input Recommendations	38
7.3	Other Characteristics	38
7.3.1	Device Impedance	38
7.3.2	Interference to Analog Signaling	40
7.3.3	Output During Silence (Interference on Digital Signaling)	40
7.4	Test Requirements	41
7.4.1	Test Loads	41
7.4.2	Analog Test Filter	43
7.4.3	Digital Test Filter	43
7.5	Cable Characteristics and Lengths	43
7.5.1	Cable Types	43
7.5.2	Recommended Minimum Conductor Size (Diameter)	43
7.5.3	Calculated Single-Pair Length	43
7.5.4	Maximum Multi-Pair Length	46
8	Non-Communicating Network Devices.....	50
8.1	Network Power Supply	50
8.1.1	Power Distribution and Barriers	51
8.1.2	Shielding and Grounding	52
8.2	Barriers	53
8.3	Miscellaneous Hardware	55
ANNEX A.	Discussion and Derivation of Specifications	57
A - 5.3	Device Connection Types.....	57
A - 6.2	Combination of Elements	58
A - 6.2.1	Rule Number 1.....	58
A - 6.2.2	Rule Number 2.....	58

A - 6.2.3 Rule Number 3.....	59
A - 6.2.4 Rule Number 4.....	59
A - 6.2.5 Rule Number 5.....	59
A - 6.3 Example Topologies	59
A - 7.1.2 Digital Signaling Characteristics	59
A - 7.1.3 Transmitted Waveform	60
A - 7.1.4 Receiver Characteristics	60
A - 7.2.1 Analog Signaling Spectrum.....	62
A - 7.2.2 Analog Signaling Interference on Digital Signaling.....	62
A - 7.3.1.1 High Impedance Devices	63
A - 7.3.1.2 Low Impedance Devices.....	64
A - 7.3.1.3 Secondary Device Impedance.....	67
A - 7.3.2 Interference to Analog Signaling.....	67
A - 7.3.2.1 Carrier Start/Stop	68
A - 7.3.2.3 Cyclic Connection Transients.....	69
A - 7.3.3 Output During Silence (Interference on Digital Signaling).....	69
A - 7.4.1 Test Loads	70
A - 7.5.1 Cable Types	71
A - 7.5.2 Recommended Minimum Conductor Size (Diameter)	71
A - 7.5.3 Calculated Single-Pair Length	71
A - 8.1 Network Power Supply	77
A - 8.1.2 Shielding and Grounding	78
A - 8.2 Barriers.....	78
A - 8.3 Miscellaneous Hardware.....	78
ANNEX B. Wire Resistance Table	79
B1. Additional Cable Length Graphs	80
ANNEX C. Document Revision History.....	88
C1. Changes from Rev 8.0 to Rev 8.1	88